

## DX6i Program Settings/Values for Blade 400 3D RTF\*

\*NOTE - All DX6i settings are the same as "default" unless specified otherwise below

### ADJUST LIST

#### D\|R&EXPO

AILE	1	90% INH
ELEV	1	90% INH

#### TRAVEL ADJ

RUDD	<- 90%	-> 90%
------	--------	--------

#### GYRO

RATE		SW- GYRO
0:	66,5%	
1:	64,0%	

### THRO CUR

STUNT	POS L	POS 2	POS 3	POS 4	POS H
	100,0%	92,5%	85,0%	92,5%	100,0%
HOLD	POS H				
	- 0.0%				

### PITC CUR

NORM	POS L	POS 2	POS 3	POS 4	POS H
	35,0%	42,5%	50,0%	75,0%	100,0%
HOLD	POS L	POS 2	POS 3	POS 4	POS H
	35,0%	42,5%	50,0%	75,0%	100,0%

#### SWASH MIX

AILE	- 75%
ELEV	- 75%
PITC	+ 85%

### SETUP LIST

#### MODEL NAME

MODEL 1  
BLADE400

#### REVERSE

AILE - R  
RUDD - R

#### SWASH TYPE

CCPM 120\*

#### TIMER

DOWN TIMER - 04:30